

ROVINCE Tire Specification Sheet

Maximum speed for counterbalanced lift truck: 25 kmph.

Maximum travel distance: restrict to 2 kms per journey

Special tyres: Non marking(grey and white) tyres are available on demand.

Electrically conductive tyres are available.



Solid Resilient Tires

Tire Size	Rim Size	Quick/ Normal	Weight (kg)	Tread Pattern	Load Capacity								
					Tire Dimensions (Inch)		Tyre Dimensions (mm)		Forklift Trucks Load Capacity (kg)		Other Vehicles (Trailers)		
					Smooth(S) Traction(TR) Rib(R.)	Max Width	O.D. +/-2%	Max Width	O.D. +/-2%	Load Wheels up to 16 km/h	Load Steering Wheels up to 25 km/h	up to 6km/h	up to 10km/h
4.00-8	3.75-8	N	12.3	R	4.7	16	119	407	950	730	950	860	730
5.00-8	3.00D-8	Q/N	17.2	TR	4.7	18	120	457	1415	1090	1415	1285	1090
15x41/2-8	3.00D-8	Q/N	9.9	TR	4.5	15	115	380	1040	800	1040	945	800
16x6-8	4.33R-8	Q/N	16.8	TR	6	16.3	153	414	1270	975	1270	1150	975
18x7-8	4.33R-8	Q/N	20.6	TR	6	17.9	153	455	2145	1650	2145	1945	1650
6.00-9	4.00E-09	Q/N	27.1	TR	5.4	20.9	136	530	1885	1450	1885	1710	1450
21x8-9	6.00E-09	Q/N	34.2	TR	7.3	20.7	185	525	2755	2120	2755	2550	2120
6.50-10	5.00F-10	Q/N	36.7	TR	6.3	22.6	160	573	2340	1800	2340	2125	1800
200/50-10	9.50F-10	Q/N	25.5	TR	7.6	18.1	194	461	2470	1900	2470	2240	1900
23x9-10	6.50F-10	Q/N	45.3	TR	8	23.3	202	592	3160	2430	3160	2865	2430
7.00-12	5.00S-12	Q/N	48.25	TR	6.7	26	170	660	2920	2240	2920	2645	2240
23x10-12	8.00G-12	Q/N	48.3	TR	9.1	23.2	231	590	3770	2900	3770	3420	2900
27x10-12	8.00G-12	Q/N	71.6	TR	9.8	27.1	248	688	3900	3000	3900	3540	3000
28x9-15	7.00-15	Q/N	60.4	TR	8.5	27.3	216	694	3445	2650	3445	3125	2650
7.00-15	5.50-15	Q/N	70.9	TR	7	28.8	179	732	3545	2725	3545	3215	2725
7.50-15	5.50-15	Q/N	75.6	TR	7.9	29.6	200	753	3900	3000	3900	3540	3000
8.25-15	6.50-15	Q/N	89.75	TR	8.3	32.3	210	821	4750	3650	4750	4300	3650
250-15	7.00-15	Q/N	76.8	TR	8.8	28.6	223	726	4745	3650	4745	4310	3650
250-15	7.50-15	Q/N	76.8	TR	8.8	28.6	223	726	4745	3650	4745	4310	3650
300-15	8.00-15	Q/N	109.6	TR	10	32.5	255	825	5850	4500	5850	5310	4500
28x12.5-15	9.75	Q/N		TR									
355/65-15	9.75-15	Q/N	135.4	TR	12	32.6	304	828	7000	5430	7000	6430	5430
10.00-20	7.50-20	N	173	S	9.7	40.2	247	1020	6000	5000	6000	5350	5000
10.00-20	7.50-20	N	173	TR	9.9	41.1	251	1045	6000	5000	6000	5350	5000

Main Office

172 E. Manville St, Compton, CA 90220
Tel: (310)885-9797 Fax: (310)885-9799

ROVINCE Tire Specification Sheet

Maximum speed for counterbalanced lift truck: 25 kmph.

Maximum travel distance: restrict to 2 kms per journey

Special tyres: Non marking(grey and white) tyres are available on demand.

Electrically conductive tyres are available.

All products are confirmed to ETRO, JATMA and TRA standards.



Press-On Tires

Tyre Designation Tire Size		Tread Design	Weight	Load Capacity(kg)					
inch	mm.	Smooth(S)/ Traction(TR)	kg	Up to 10 km/h		Up to 16 km/h		Up to 25 km/h	
				Load Wheels	Steering Wheels	Load Wheels	Steering Wheels	Load Wheels	Steering Wheels
9x5x5	228.6x127x127	S	7	1065	875	950	800	-	-
10x5x6 1/2	254x127x165.1	S	7.49	1010	840	905	830	-	-
13 1/2x5 1/2x8	342.9x139.7x203.2	S	13.51	1505	1250	1345	1240	-	-
14x4 1/2x8	356x114-203.2	S	11.5	1170	960	1045	875	850	695
14x5x10	356x127-254	S	12.12	1490	-	-	-	-	-
15x5x11 1/4	381x127-285.8	S	12.81	1290	1140	1240	1040	1010	830
16x5x10 1/2	406x127-266.7	S/TR	16	1510	1240	1345	1130	1095	895
16x6x10 1/2	406x152-266.7	S/Semi Track	18.67	1910	1570	1710	1435	1390	1140
16 1/4x5x11 1/4	413x127-285.8	S/TR	15.02	1530	1250	1360	1145	1105	905
16 1/4x6x11 1/4	413x152-285.8	S/Semi Track	18.43	1920	1580	1715	1440	1395	1140
18x5x12 1/8	457x127-308	S	19.03	1640	1350	1470	1230	1195	980
18x6 x12 1/8	457x152-308	S/TR	22.3	2110	1720	1870	1575	1525	1250
18x7x12 1/8	457x178-308	S/TR	26.83	2550	2100	2280	1910	1855	1520
21x7x15	533x178-308	S/TR	32.55	2875	2350	2560	2450	2085	1710
21x8x15	533x203-381	S/TR	36.7	3375	2775	3025	2540	2455	2015
22x8x16	559x203-406.4	S	38.67	3500	2875	3130	2625	2545	2085
22x9x16	559x229-406.4	S/TR	44.45	4050	3325	3600	3025	2930	2400
22x10x16	559x254-406.4	S	-	4575	3750	4080	3425	3315	2720
22x12x16	559x305-406.4	S	58.64	5625	4625	5030	4225	4090	3350
22x14x16	559x356-406.4	S	69.83	6657	5466	6000	5040	-	-
22x16x16	559x406-406.4	S	77	7760	-	-	-	-	-
28x10x22	711x254-558.8	S	69.4	5727	4460	-	-	-	-
28x12x22	711x305-558.8	S	77.56	6785	5574	5990	5550	-	-
28x14x22	711x356-558.8	S	91.98	7966	6543	7150	6020	-	-
28x16x22	711x406-558.8	S	-	-	-	-	-	-	-
40x10x30	1016x254-762	S	138	-	-	-	-	-	-
40x12x30	1016x305-762	S	168	8760	-	-	-	-	-

Main Office

172 E. Manville St, Compton, CA 90220

Tel: (310)885-9797 Fax: (310)885-9799